

# PROFORMANCE<sup>®</sup>

**HIGH INTENSITY AIR DISINFECTION SYSTEMS**

The PROfessional's Choice For Extreme Microbial Control



## PRO-100-DR

REMOTE MULTIVOLTAGE  
UV GERMICIDAL AIR PURIFIER

### Highlights

- Two powerful germicidal twin-tube U lamps output up to six times more microwatts than a single-tube lamp.
- Moisture-proof lamp connector and mid-cord connector.
- Remote units fit in tight spaces.
- Auto-sensing ballast works from 120 VAC to 240 VAC.
- 12" or 16" UV lamps available for correct fit.
- 280 Microwatts (two 12" lamps).
- 360 Microwatts (two 16" lamps).
- Lifetime warranty on electronics,
- 2-year warranty on lamps
- ETL certified

### Available Accessories

- Magnetic Z brackets and lamp reflectors for germicidal lamp mounting.
- Offset duct-board mounting plate for duct board mounting the remote germicidal lamp.
- Current sensing switch to interlock UV units with the blower motor in an air handler or furnace.



### REMOTE POWER SUPPLY SPECIFICATIONS

#### PRO-100DR

Power supply dimensions: Size (L x W x D) 10.5h x 5.75w x 1.5 d  
Auto-sensing multivoltage ballast 120 - 240 VAC 50/60 HZ.  
100 WATT .40/.20 AMP

16" Germicidal U lamps penetrates duct 15.5"  
12" Germicidal U lamps penetrates duct 12.25"

### GERMICIDAL LAMP SPECIFICATIONS

16" Twin-Tube Germicidal U Lamp	36 watts, 425 mA 180 μW/cm <sup>2</sup>
12" Twin-Tube Germicidal U Lamp	24 watts, 425 mA 140 μW/cm <sup>2</sup>
Rated Life	2 years
Lamp Dimensions	13" or 16.5" from base to end
Glass Diameter	30 mm (15 mm x 2)



For Critical Applications Use Porex™ Virtek™ Reflective Media For Optimal Performance



[www.PROformancelAQ.com](http://www.PROformancelAQ.com)