



The PROfessional's Choice For Extreme Microbial Control



















REMOTE MULTIVOLTAGE UV GERMICIDAL AIR PURIFIER WITH ODOR CONTROL

# **Highlights**

- Powerful germicidal twin-tube U lamp outputs up to three times more microwatts than a single-tube lamp.
- Our patented oxidizing chamber uses activated oxygen for odor control.
- Odor control is easily adjustable by the homeowner.
- Helps to eliminate household odors.
- Remote units fit in tight spaces.
- LED lamp monitor lets you know at a glance the UV lamp is operating.
- Moisture-proof lamp connector and mid-cord connector
- Remote units fit in tight spaces.
- 12" or 16" lamps for correct fit.
- 140 Microwatts (single 12" lamp).
- 180 Microwatts (single 16" lamp).
- Lifetime warranty on electronics
- 2-year warranty on lamps.
- ETL certified

#### **Available Accessories**

- Magnetic Z brackets and lamp reflectors for germicidal lamp mounting.
- Offset duct-board mounting plate for duct board mounting the remote germicidal lamp.
- Current sensing switch to interlock UV units with the blower motor in an air handler or furnace.





### REMOTE POWER SUPPLY SPECIFICATIONS

#### PRO-50-DR

Power supply dimensions: Size (L x W x D) 6h x 5.75w x 1.75 d Auto-sensing multivoltage ballast 120 - 240 VAC 50/60 HZ. 50 WATT .40/.20 AMP

Remote Lamp Socket Dimensions: Size (L x W) 3.5" x 2.75"

16" Germicidal U lamps penetrates duct 15.5" 12" Germicidal U lamps penetrates duct 12.25"

PRO-7-50OU size (L x W x D) 4" x 4" x 3.75" Odor control chamber penetrates duct 4.5"

## **GERMICIDAL LAMP SPECIFICATIONS**

16" Twin-Tube Germicidal U Lamp 36 watts, 425 mA 180 μW/cm2 12" Twin-Tube Germicidal U Lamp Rated Life

Lamp Dimensions Glass Diameter

5" UVV Lamp 8 watts, 425 mA

Output at 184 nanometers 50 mg per hour maximum Rated life 2 years Lamp dimensions 5" from base to end

2 years

Quartz diameter 15 mm (T5)





24 watts, 425 mA 140 μW/cm2

13" or 16.5" from base to end

30 mm (15 mm x 2)